AUTOMATOR ATF VI

Transmissions and Gearboxes

Description

AUTOMATOR ATF VI s a low viscosity and fully synthetic lubricant approved by General Motors for use in all their automatic transmissions, exceeding Dexron III, Dexron II and TASA. Recommended for light vehicles, commercial vehicles and some heavy duty.

Properties

- Low viscosity fluid for maximum fuel economy compared with fluids that meet DEXRON III.
- Improves performance and service life compared to previous automatic transmission fluids (ATF), thus reducing maintenance.
- Compatible with joints and seals.
- Excellent oxidation resistance which reduces deposit formation and prolongs transmission life.
- Ensures smooth, silent gear change and efficient power transfer under all service conditions thanks to its friction modifiers.

Quality levels, approvals and recommendations

- GM DEXRON VI *
- FORD MERCON LV
- JASO M315 1A-LV
- Aisin Warner JWS 3309 (T-IV) & JWS 3324 (WS), AW-1
- Audi 5 HP LT71141
- BMW JWS 3309 (T-IV)
- BMW LA2634
- BMW ETL-8072B
- BMW LT 71141 (ZF 5 HP 18FL/19FL/24A)
- Chrysler/Dodge MOPAR AS 68 RC (T-IV), JWS 3309
- FIAT T-IV type, JWS 3309
- Ford FNR5 (Mazda M5, XT-9-QMM5)
- Honda ATF-Z1 (except in CVTs)
- Honda DW-1
- Hyundai/Kia SP-III, SP-IV
- Hyundai/Kia SP-IV M (SP4-M)
- Hyundai/Kia SP-IV-RR
- Nissan Matic Fluid C, D, J, K, S
- ISUZU BESCO ATF-II, ATF-III, ATF SP
- Jaguar ATF 3403-M115
- Jaguar ATF LT71141, ZF 5HP24
- Jaguar ATF 3403, JLM20238
- Mazda ATF M-III, M-V
- Mitsubishi Diaqueen SK, SP-II, SP-III
- Opel (all vehicles)
- Peugeot ZF 4HP20
- Peugeot/Citroen (PSA) AL4 Automatic gearbox oil (#9730.AE)
- Porsche ZF 5HP19FL, ZF 5HP20, LT71141
- Porsche ATF 3403-M115,
- Porsche T-IV (JWS 3309)
- Saab T-IV (JWS 3309)

AUTOMATOR ATF VI

- Saab 93 165 147
- Subaru ATF 5AT
- Subaru ATF, ATF HP
- Suzuki ATF 2326
- Toyota ATF D-II, D-III
- Toyota ATF T-III, T-IV
- Toyota ATF WS
- Volvo CE 97340
- VW 5 HP (ZF 5 HP 30)
- VW 5HP (18FL, 30)
- VW 5HP (19FL, 24A)
- VW G 055 025 A2 (JWS 3309)
- VW G 055 162-A2, A6 (ZF lifeguard fluid 6 Plus)
- VW G 060 162- A2 (ZF lifeguard fluid 8)
- VW G 052 162 (ZF Lifeguardfluid 5)
- VW TL 521 62
- ZF 8 speed transmissions
- ZF 9 speed transmissions
- ZF TE-ML 05L, 09, 11A, 11B, 21L

* Formal approval

Technical specifications

	UNIT	METHOD	VALUE
Colour	Visual		Red
Density at 15 ºC	g/cm3	ASTM D 4052	0,847
Viscosity at 100 ºC	cSt	ASTM D 445	6
Viscosity at 40 ºC	cSt	ASTM D 445	30
Viscosity at -40 ºC	cP	ASTM D 2983	< 15000
Viscosity index	-	ASTM D 2270	151
Flash point, open cup	ºC	ASTM D 92	216
Pour point	ºC	ASTM D 97	-49

The above mentioned characteristics are typical values and should not be considered product specifications.